



## **GAMELINER™ COURT FLOOR PAINT**

GAMELINER™ COURT FLOOR PAINT was developed exclusively for court floor surfaces. It is a fast drying, high solids, solvent based paint that is compatible with both the POLYDEFENDER™ and AQUADEFENDER™ coating systems. GAMELINER™ COURT FLOOR PAINT is the perfect choice for painting game lines, solid painted borders, and graphics on court floor surfaces. It has excellent leveling properties, chip resistance, and hide. This product contains less than 450 grams per liter VOC (volatile organic compound).

USE DIRECTLY FROM CONTAINER - DO NOT DILUTE

GAMELINER™ COURT FLOOR PAINT WILL ADHERE TO MOST SURFACES IF DRY AND PREPARED PROPERLY. BE SURE TO ALWAYS PREPARE A TEST AREA TO ENSURE COMPATIBILITY.

ABRADING USING DEFENDER™ BLUE PADS OR SCREENS: WHEN ABRADING IS REQUIRED BE SURE TO ROTATE DEFENDER™ BLUE PADS OR SCREENS AT A RATE OF 500 SQUARE FEET - 250 SQUARE FEET EACH SIDE.

PAINTING CONDITIONS: Use when temperature is above 32°F and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 100°F.

### **PREPARATION:**

Sand and prepare floors according to MFMA accepted methods. The prior seal or finish coat should be abraded using 120 or 150 grit screens to ensure paints adhere properly (follow seal or finish instructions).

### **APPLICATION:**

The paint should be applied the same day the floor is abraded. Tape the floor using 3M #2090 Blue Painters Tape. Stir paint thoroughly and apply an even coat with the grain of the wood using 1/4" nap roller. For best results strike the newly painted area with a foam paint brush immediately after application. Paint should be applied at approximately 580 square feet at 1 mil dry per gallon. Allow the paint to dry 24 hours before coating with finish or second coat of paint (if needed). Dry times can be extended with high humidity and/or low temperatures. Be sure to test the paint for dryness prior to applying finish or second coat of paint. If paint has not dried thoroughly wrinkling may occur after next coat is applied. After the paint has dried thoroughly abrade the entire court floor and newly painted areas using DEFENDER™ BLUE PADS. If paint has dried longer than 48 hours abrade with used 120 or 150 grit screens. Vacuum and tack entire floor until dust free and apply final coats of AQUADEFENDER™ or POLYDEFENDER™ WOOD FLOOR FINISH (SEE PRODUCT INSTRUCTIONS). IF USING ANOTHER MANUFACTURER'S FINISH TEST A SAMPLE AREA FOR COMPATIBILITY.

RECOAT TIMES: May recoat when fully dry, usually 24 hours. Dries to touch in 2-4 hours and to handle in 5-10 hours, at 77° F - 50% relative humidity. Allow more dry time for cooler temperatures and higher humidity.

CLEAN UP: Use mineral spirits.

COVERS: 580 sq. ft. at 1 mil dry per gallon.

**WARNING:** Contains Petroleum Distillates. Vapor Harmful. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Do not breath vapors, spray mist, sanding dust, or overspray. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION. Prevent buildup of vapors by opening all windows and doors to achieve cross-ventilation. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. **WARNING:** This product contains chemicals know to the state of California to cause cancer and birth defects or other reproductive hard. KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

DOES NOT CONTAIN LEAD

CATEGORY: INDUSTRIAL MAINTENANCE COATINGS

MAX VOC: 450 g/l

FOR PROFESSIONAL USE ONLY.

**DANGER:** Rags, steel wool, or waste soaked with GAMELINER™ COURT FLOOR PAINT may spontaneously catch fire if improperly discarded. Immediately after use place rags, steel wool or waste into sealed water filled metal container.

**NOTE:** There are no express or implied warranties, including warranties of merchantability or fitness for a particular purpose. Buyer's remedies are limited to replacement or refund of purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability or product for intended use.

BEFORE USING READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS FOR THIS PRODUCT.

MADE IN USA

COURTSPO RTS INC. Toll Free 877-929-6677 Fax 360-834-3837 [www.courtfloors.com](http://www.courtfloors.com) © 2009 COURTSPO RTS INC.